



Tsunami® GX800

Wireless Product Portfolio

- **Tsunami® 8000 Series** – PtP & PtMP product line delivering 300 Mbps plus data rate
- **Tsunami® .11 Series** – Our best selling Point-to-point and multipoint product line
- **Tsunami® QB 62000**– High capacity, small footprint PtP backhaul solution with 1Gbps throughput
- **ORiNOCO® AP** - The industry's highest performance 802.11a/b/g/n access points

Proxim Wireless is a global pioneer of end-to-end broadband wireless systems that deliver quadruple play services. From Wi-Fi to wireless Gigabit Ethernet – our WLAN, mesh, WiMAX and point-to-point products are available through our extensive global channel networks.

Tsunami® GX800 is a high speed Point-to-Point (PtP) licensed microwave product capable of operating in 6–23 GHz licensed bands with more than 600Mbps aggregate throughput capacity, supporting an array of user configurable channel bandwidths from 7-56 MHz. The product has an extremely small foot print and comes in a split-mount design constituting of a compact indoor unit (IDU) and outdoor unit (ODU) that are a snap to install.

The Tsunami® GX800 Series is an outcome of Proxim's extensive RF technical expertise and years of broadband wireless access products experience. The GX800 Licensed Point-to-Point products are technically advanced, highly reliable and very cost effective.

The Tsunami® GX800 uses highly advanced radio technology. The product is designed for PDH and Wireless Broadband applications, utilizing modulation schemes from QPSK to 256QAM and high data rates. The product supports High Transmit Power Levels with up to +27dBm for certain frequency bands. The product is optimized for high speed Ethernet networking and for transmission of standard E1 or E3 channels.

Tsunami® GX800 is not just another typical PDH platform. It houses a unique innovative proprietary packet system with different priority for each transmission channel. This advanced prioritization platform intelligently allocates transmission capacity depending on modulation scheme and channel bandwidth controlling adaptive selection of user interfaces and their speeds.

Advantages and key features

- 6-23 GHz Frequency band support
- Wide band support from 7-56MHz RF Channel Bandwidths
- Supports QPSK/16QAM/32QAM/64QAM/128QAM/256QAM Modulation schemes
- High Tx Power radio
- Low noise figure, low phase noise and high linearity
- Compact and lightweight design, the smallest IDU in its class
- Very high frequency stability +/- 5 ppm
- Wide operating temperature range for ODU: -45 to +55°C
- Up to 16xE1 or 1xE3, one Gigabit Ethernet and one Fast Ethernet traffic interfaces with true traffic capacity from 5Mbps up to 622Mbps.
- Capacity is dynamically allocated between E1/E3 channels and Ethernet
- Features ATPC and Adaptive Modulation (user defined)
- Built-in Spectrum Analyzer, BER Tester, and Throughput, WAN Utilization charts
- ODU features standard direct 'slip fit' mounting
- Fully supported by Proxim Vision ES Network Management Solution
- Designed to meet FCC, ETSI and CE safety and emission standards
- Supports popular ITU-R standards and frequency recommendations

PRODUCT SERIES	Tsunami® GX800 Product Family		
GX800-6U/L	Tsunami GX800, 6U/6LGHz Microwave Link Series		
GX800-07	Tsunami GX800, 7GHz Microwave Link Series		
GX800-08	Tsunami GX800, 8GHz Microwave Link Series		
GX800-10/11	Tsunami GX800, 10/11GHz Microwave Link Series		
GX800-13	Tsunami GX800, 13GHz Microwave Link Series		
GX800-15	Tsunami GX800, 15GHz Microwave Link Series		
GX800-18	Tsunami GX800, 18GHz Microwave Link Series		
GX800-23	Tsunami GX800, 23GHz Microwave Link Series		
RADIO & TRANSMISSION			
FREQUENCY BANDS			
	Frequency Band (GHz)	Frequency Range (GHz)	T/R Spacing (MHz)
	6U/L	5.925 - 7.110	160, 170, 252.04, 300, 340, 350
	7	7.125 - 7.725	154, 160, 161, 168, 196, 245
	8	7.9 - 8.5	119, 126, 208, 266, 311.32
	10/11	10.7 - 11.7	350, 490, 500, 530
	13	12.75 - 13.25	266
	15	14.4 - 15.4	315, 420, 475, 490, 640, 644, 728
	18	17.7 - 19.7	1008, 1092.5, 1010, 1560
	23	21.2 - 23.6	1008, 1200, 1232
CHANNEL BANDWIDTH	Wideband support. Configurable from 7-56MHz <ul style="list-style-type: none"> • CEPT/ETSI: 7, 14, 28, 56MHz • ANSI/FCC: 10, 20, 30, 40, 50MHz 		
MAX TX POWER	27 dBm		
TX POWER CONTROL	1 dBm Steps and Supports ATPC		
MAX RX SENSITIVITY	-90 dBm		
MODULATION	QPSK, 16QAM, 32QAM, 64QAM, 128QAM, 256QAM		
ERROR CORRECTION	FEC, Predistortion, Equalization, Internal BER		
FREQUENCY STABILITY	±5 ppm		
EMISSION DESIGNATOR	30M0D1D (ANSI), 28M0D1D (ETSI)		
BRIDGING & DATA INTERFACES			
TRAFFIC INTERFACES	Gigabit Ethernet 1000Mbps Base T (RJ45) + One 100Mbps Fast Ethernet HSI Module Interface Options: nxE1, nxT1, nxE3, nxT3		
THROUGHPUT CAPACITY	622Mbps		
LATENCY	100 µs – 400 µs		
VLAN, QOS	IEEE 802.1Q, 802.1p QoS		
MANAGEMENT			
CHANNEL	Inband and out-of-band		
SNMP	SNMP v1/v2c, Manageable via Proxim Vision ES		
TELNET	IP Based via dedicated NMS port		
SERIAL	Craft/RS232 Port		
HTTP	Web based GUI		
USB	2 USB Ports. USB port A can be used for connecting USB flash card for configuration store/restore, firmware upgrade and to download log files from device. USB port B is used for device debug Management by Proxim		
Out-of-band interface	10 / 100 Base T Fast Ethernet Port (RJ-45)		
PHYSICAL			
DIMENSIONS	IDU : 10.0 x 1.73 x 7.9 in (Std 19" Half rack mount & 1U height) ODU : 10.9 x 9.4 x 3.6 in		
WEIGHT	IDU : 2.6 lbs ODU : ≤ 9.5 lbs		
POWER			
POWER INPUT	-48 VDC (EN 300 132-2)		
MAX POWER CONSUMPTION	60W Max. (IDU + ODU)		
ENVIRONMENTAL			
OPERATING TEMPERATURE	IDU: ETS 300 019 Class 3.2 (-5 to +45°C) ODU: ETS 300 019-2-4 Class 4M5 (-45 to +55°C)		
RELATIVE HUMIDITY	up to 95% (non-condensing)		
MTBF & Warranty	200,000 hours & 2 year parts and labor		
REGULATORY	ETSI/FCC Compliant CE Mark Certification 50 Year Recyclable Compliant ROHS-Compliant		